



PFC Corofil Intumescent Silicone Putty

Intumescent Silicone Putty

PFC Corofil Intumescent Silicone Putty can be used to form a water proof and fire resistant seal around pipe and cable penetrations. Tested to BS:EN 1366-3, the putty has been shown to provide up to a 4 hour fire rating.

- Easy to install
- Ideal for sealing around cables in electrical trunking
- No maintenance
- No smoke emission
- Easy to remove and reinstate for new services

Description

PFC Corofil Intumescent Silicone Putty is a red, non-setting compound.

It can be cut and moulded between metal pipes and cable penetrations to plug holes in compartment walls and floors. PFC Corofil Intumescent Silicone Putty is particularly useful in sealing cable bunches in trays and electrical trunking. Due to its' non-setting nature it remains malleable, so it can easily be removed and replaced to accommodate the introduction and removal of future service runs.

In a fire, the putty intumesces to fill small gaps between services, but does not emit any hazardous smoke.

Before installing the putty, substrates must be thoroughly dry, clean and free of grease and other contaminants.

Fire Rating

Up to 4 hour fire rating in floors and walls with metal pipes, steel electrical trunking and cables at a depth of 100mm.

Packaging

PFC Corofil Intumescent Silicone Putty is packaged in 1 kg tubs.

Specification

Install PFC Corofil Intumescent Silicone Putty around cable trays and internally within metal electrical trunking. Installation to be fully in accordance with manufacturer's instructions.

To order

Please contact our technical sales office (Tel: +44 (0) 208 391 0533) with the number of 1 kg tubs you require.



NSPlus