



# Butyl Tape

## Application

PFC Corofil Butyl Tape is a pre-formed, polyisobutylene (PIB) based sealing tape.

The strip can be used to seal dry wall track where they interface with construction soffits and floors

## Product Data

<b>Colour</b>	White
<b>Dimensions</b>	3mm thick x 25mm wide x 3.6 linear metres long
<b>Shelf Life</b>	18 months in ambient conditions
<b>Service Temperature Range</b>	-40°C to +90°C
<b>Joint Movement</b>	Up to 15%

## TECHNICAL INFORMATION

Available from our technical sales office.

Email [tech@pfc-corofil.com](mailto:tech@pfc-corofil.com) for:

- Safety Data Sheet (SDBUTYL)
- Installation Instructions (MSBUTYL)

Please order from our technical sales office.

PFC Corofil  
Units 3-4  
King George Trading Estate  
Davis Road  
Chessington  
Surrey KT9 1TT

Tel: + 44 (0) 208 391 0533  
Fax: + 44 (0) 208 391 2723  
Email: [sales@pfc-corofil.com](mailto:sales@pfc-corofil.com)  
[www.pfc-corofil.com](http://www.pfc-corofil.com)



*This data sheet shows the only applications the product has been tested in. Please ensure the product has been tested in, and is suitable for your application (see PFC Corofil terms and conditions 13.1.1).*

Doc Reference				TDBUTYL			
PB	SE	CB	CI	AB	IFC		
This Copy				Review Date			
November 2018				November 2020			